

Super 10 LA



Super 10 Low Angle 10°
Blue Nozzle Body



Super 10 Low Angle 14°
Red Nozzle Body

Undertree sprinklers

Low angle, Low-volume, ball-driven sprinkler
1/2" male

Regulated - silver base

Non regulated - black base

Applications: orchards, vineyards and banana plantations.

- Available with two different low angles 10° and 14°
- High-impact, heavy-duty plastic materials provide resistance to corrosion fertilizers and UV radiation
- Compact, sturdy, closed and protected ball engine
- Color-coded bayonet nozzle for easy operation and service
- Optional Flow Regulator
- Operating pressure – 2.5-4.0 bar w/o regulator
3.0-5.0 bar with regulator



Super 10 LA PERFORMANCE TABLE

Nozzle color	P (bar)	Q (l/h)	Super 10 Low angle 10° Blue nozzle body		Super 10 Low angle 14° Red nozzle body	
			D (m)	msh (cm)	D (m)	msh (cm)
Violet	2.5	360	15.5	60	17.5	90
	3.0	395	16	62	18	99
	3.5	425	16	64	18	111
	4.0	455	16	68	18	114
F.R.	3.0-5.0	360	15.5	60	17.5	90
Yellow	2.5	450	16.5	50	17.5	100
	3.0	495	16.5	55	18	105
	3.5	530	17	60	18	110
	4.0	570	16.5	65	17.5	115
F.R.	3.0-5.0	450	16.5	50	18.5	100
Green	2.5	550	16	55	16	105
	3.0	600	16.5	60	17.5	110
	3.5	650	17	70	18	115
	4.0	695	16.5	80	18.5	120
F.R.	3.0-5.0	550	16.5	60	18	100
Red	2.5	670	16.5	60	18.5	110
	3.0	735	17	65	19	115
	3.5	790	17.5	70	19	120
	4.0	850	17	80	19	125
F.R.	3.0-5.0	670	17	70	19	120

msh = max. stream height (above nozzle)

* Performance table prepared under laboratory conditions

* For windy conditions use closer spacing

PRODUCT RANGE

Nozzle color (mm)	Q (l/h)	Super 10 Low angle 10° Blue nozzle body		Super 10 Low angle 14° Red nozzle body	
		Super 10 Catalog no.	Super 10 Regulated Catalog no.	Super 10 Catalog no.	Super 10 Regulated Catalog no.
Violet	360	335344	336344	335744	336744
Yellow	450	335346	336346	335746	336746
Green	550	335342	336342	335742	336742
Red	670	335347	336347	335747	336747

Super 10 Regulated with silver base